

Model LCT-5620 (5620G) Reference No: 251384NTU Utility Expo 2023



OVL Length: 15 Appx Wgt +/-: 3,440 lbs

Item Type	Options	Description	Add Qty	Unit	Total Qty
Base Trailer		LCT-5620 (5620G)		Each	0
Reel Capacity		Reel Diameter Capacity: Up to 44" Wide Reels – 13' Maximum / 44" – 60" Wide Reels – 12' Maximum - Reel Width Capacity: 56" with bushings/collars installed / 60" without bushings/collars		Std	1
Deck Type		Pressure Treated Wood		Std	1
Overall Length		Overall Length in Feet		Feet	14.5
Overall Height		6' 8" Overall Height		Std	1
Width		102" OD, 60" ID		Std	1
Brakes		Electric, FSA (Fwd Self Adj) On All Axles		Std	1
Axles		8K Oil Bath		Std	1
Suspension		Rubber Torsion		Std	1
Tires & Wheels		235/75R 17.5 J, 8 Bolt [17.5 x 6.75] Plate Wheel		Each	2
Reel Turning Tires		Reel Turning Tires - 18.5 x 8.5-8		Std	2
Hitch Type		3" Adjustable Lunette Eye/Pintle, [C] Channel Mount		Std	1
Hitch Length		Coupler to Headboard, Appx		Std	6
Jack		8k Side Wind Jack w/ Drop Leg and Mount Plate		Std	1
Stabilizer Jack		Rear Stabilizer Legs		Pair	1
Plug		7 Pole RV		Std	1
Lights		LED Lights, Sealed Wiring Harness		Std	1
Hydraulic System		V-Twin Gas Engine with a 2-stage hydraulic system for high speed or high torque		Std	1
Trailer Color		Galvanized		Std	1
Standard		3/8" Safety Chains, Grade 70		Std	1
Standard		Auxiliary quick couplers for operating hydraulic tools		Std	1
Standard		Arbor with a set of bushings and lock collars for single reel		Std	1
Standard		Hand brake on the reel turning axle		Std	1
Standard		5,600 lb. Payload Capacity		Std	1
Option	✓	Ramps & Ramp Storage (7097A)		Opt	1
Option	✓	Cold Weather Start Kit (HYD-KIT-H)		Opt	1
GVWR		8,000 lbs		Std	1